



WALL MOUNTED VENT FREE FIREPLACE (RDS)

- 22,000 BTU
- Dual Fuel Technology, uses LP or Natural Gas
- Controls hidden behind trim
- Infinite turn down
- Stylish stainless steel front face with glass
- 38"W x 26.75"H x 12"D



ADI 10 - 10K BTU BLACK INSERT

- 10,000 BTU
- Zero Clearance
- Dual Fuel Technology, uses LP or Natural Gas
- Remote capable
- Available as an insert or with a mantel

MANTELS

- | | |
|--------|----------------|
| AMF-CC | Cherry Cabinet |
| AMF-LM | Distressed Oak |



ARCHED VENT FREE FIREPLACE INSERT

- 20,000 BTU
- Realistic log and burner design
- Compact arch fireplace perfect for kitchens and offices
- Millivolt control
- 50% turndown for greater control
- Multiple mantel design for versatility and placement



A-SERIES INSERT

- | | |
|--------|----------------------------|
| ANI | 20K BTU Black Insert, NG |
| ALI | 20K BTU Black Insert, LP |
| AF-C | Cherry Floor Mantel |
| AF-LM | Light Maple Floor Mantel |
| AFC-C | Cherry Corner Floor Mantel |
| AFC-LM | Light Maple Floor Mantel |
| AT-C | Cherry Tower Mantel |
| AT-LM | Light Maple Tower Mantel |
| ATC-C | Cherry Corner Tower Mantel |
| ATC-LM | Light Maple Tower Mantel |



DIS Vent Free Insert



DIS 33 Vent Free Gas Fireplace Insert System Remote Ready			
Millivolt control valve with on/off switch and manual variable flame height control			
DIS33NVG	28,000 BTU	NG	Vent Free Insert Millivolt control w/Blower
DIS33PVG	28,000 BTU	LP	Vent Free Insert Millivolt control w/Blower

Triple Play Burner System™ with exclusive triple effect technology

- Designed to fit most masonry fireplaces, fitting a minimum fireplace opening of 24" H and 33" W
- Thermostatically controlled blower (135 cfm)
- Fiber ceramic cottage clay firebrick and standard black removable louver system
- Integrated Safety Shut-off Valve
- No venting required for easy installation
- Heats up to 950 sq. ft., all the heat stays in your home.

Field Installed Accessories

- 33" Polished Brass Louvers. Stock # **DIS33LBR**
- 36" H x 50" W Black Face Plate with Brass Trim. Stock # **DIFACE-LG**
- 33" H x 43" W Black Face Plate with Brass Trim. Stock # **DIFACE-SM**



CFX CHESAPEAKE VENT FREE SYSTEM



- Comes complete and ready to install with logs, firebox and cabinet
- Features the Triple Play Burner System®; loose embers, glowing logs and yellow flame all in one
- Cabinet available in dark cherry or classic white
- 24" and 32" wide fireplace systems
- (22,000), or (26,000) BTU models
- Millivolt control operations
- CSA design certified

Model #	Description
CFX24NVW	24" Chesapeake Vent Free System, Natural Gas w/ White Wall Cabinet
CFX24PVW	24" Chesapeake Vent Free System, Propane Gas w/ White Wall Cabinet
CFX24NVDC	24" Chesapeake Vent Free System, Natural Gas w/ Dark Cherry Cabinet
CFX24PVDC	24" Chesapeake Vent Free System, Propane Gas w/ Dark Cherry Cabinet
CFX32NVW	32" Chesapeake Vent Free System, Natural Gas w/ White Wall Cabinet
CFX32PVW	32" Chesapeake Vent Free System, Propane Gas w/ White Wall Cabinet
CFX32NVDC	32" Chesapeake Vent Free System, Natural Gas w/ Dark Cherry Cabinet
CFX32PVDC	32" Chesapeake Vent Free System, Propane Gas w/ Dark Cherry Cabinet

DFS Vent Free Gas Fireplace System

- Full size fireplace system with 32", 36" and 42" hearth openings
- **Triple Play Burner System™** with exclusive triple effect technology producing a full random yellow flame, full depth ember bed, and glowing logs
- Factory or field installed cottage clay firebrick or field installed cottage red firebrick
- Fixed screen, integrated burner assembly, concealed controls, black louvers, black medium trim, flex connector and junction box
- No venting required, all the heat stays in the home
- New air duct design allows blower operation with optional radiant face plates
- "Remote Ready" Millivolt control with manual variable height adjustment

Factory Install Options

- Forced Air Blower - BTC Variable Thermostat controlled Forced Air Blower, 160 cfm.
- Louvers - L Polished Brass Louvers.
- Wire - W 15 feet of wire for Wall Switch (Millivolt model only)
- Cottage Clay Firebrick - F 32" Cottage Clay firebrick-Ceramic Fiber.
36" Cottage Clay firebrick-Ceramic Fiber.
42" Cottage Clay firebrick-Ceramic Fiber.



DFS32NVC, DFS32PVC
 DFS36NVC, DFS36PVC
 DFS42NVC, DFS42PVC



BUF UNIVERSAL VENT FREE FIREBOX

- 36" and 42" vent free firebox, includes junction box
- Circulating firebox with radiant clean and optional blower
- Optional outside air kit available
- Standard refractory brick lining and junction box
- CSA design certified to ANSI Z21.91A2002 Universal Firebox standard

Vent Free Fireboxes		
Part #	Actual (W x H x D)	Framing (W x H x D)
BUF400	40" x 34" x 21"	40 1/4" x 34 1/4" x 20 3/4"
BUF500	46" x 34" x 21"	46 1/4" x 34 1/4" x 20 3/4"



GCUF32CF, GCUF36CF and GCUF42CF Vent Free Fireboxes

- 32", 36" and 42" universal vent free fireboxes
- CSA design certified for use with 18", 24" and 30" vent free gas logs
- Out-of-the-box ready for a circulating installation
- Optional radiant panels for easy field conversion
- New air duct design allows blower operations with optional radiant face panel
- Cottage Clay firebrick

Vent Free Fireboxes			
Part #	Actual (W x H x D)	Framing (W x H x D)	Optional Radiant Panel Kits
GCUF32CF	37" x 34 1/2" x 16"	37 1/4" x 35" x 15 1/2"	CF32RPK
GCUF36CF	41" x 34 1/2" x 18"	41 1/4" x 35" x 17 1/2"	CF36RPK
GCUF42CF	47" x 37 3/8" x 18"	47 1/4" x 35" x 17 1/2"	CF42RPK

DIRECT VENT GAS FIREPLACES

Napoleon's Direct Vent Gas Fireplaces



Napoleon's Direct Vent Gas Fireplaces do not require a chimney and can be vented directly through a wall or roof. The direct vent draws its combustion air from outside while venting to the same outside atmosphere - thereby not consuming warm house air, nor competing with other appliances and furnaces for combustion air. Direct venting also eliminates drafts and heat loss associated with other fireplaces.

- Heavy gauge pan burner system and realistic, ceramic fibre, light-weight molded PHAZER™ log set for a natural wood burning look
- Equipped with 100% SAFE GUARD™ gas control system
- Available in Natural Gas or Propane
- No electricity required to light or operate – millivolt system ensures reliable use even during power failures
- President's Limited Lifetime Warranty

BGD36 - 36" Direct Vent Fireplace



- Clean, clear, louvre-free view
- Up to 17,000 BTU's top or rear vent
- Hideaway™ door allows easy access to the hidden control panel
- Built-in adjustable flame and heat control

GD33 - 33" Direct Vent Gas Fireplace



- 79.4% steady state high efficiency, 63% AFUE and up to 22,000 BTU's
- Tested as a heater and wall furnace
- No electricity required to light or operate - millivolt system ensures reliable use even during power failures
- Turn on and off at the flick of a switch
- 50% flame/heat adjustment for maximum comfort and efficiency
- A clear, unobstructed view through high-temperature, heat-radiating, ceramic glass (16" x 30 5/8")
- Concealed, easy to use controls for trouble-free performance

BGD36CF - 36" Clean Face Direct Vent Fireplace



- Clean, clear, louvre-free view
- Up to 17,000 BTU's top or rear vent
- Hideaway™ door allows easy access to the hidden control panel
- Built-in adjustable flame and heat control

DIRECT VENT GAS FIREPLACES



BGD36CFG - 36" Crystallo™ Direct Vent



- The Crystallo™ combines a polished clean face look with a unique flame and ember bed
- Our exclusive CRYSTALLINE™ ember bed sparkles with modern elegance
- CRYSTALITES™ come standard with the unit and accent the firebox from underneath the glass ember bed
- Porcelain Radiant Reflective panels are standard with the unit and echo flames and crystal reflections throughout the firebox
- Up to 17,000 BTU's
- Cost saving electronic ignition gas valve with battery back-up
- Convenient on/off switch and built-in adjustable flame/heat control
- Hinged heat resistant glass door
- Certified for bathrooms, bedrooms, bed sitting rooms and mobile homes

GD70 - 36" Starfire™ Direct Vent Gas Fireplace



- 81% steady state maximum efficiency with up to 35,000 BTU's
- 50% flame/heat adjustment for maximum comfort and efficiency
- A large 682 square inch viewing area with heat radiating ceramic glass
- Heat circulating blower with variable speed and thermostatic control
- Comes complete with an exclusive Night Light™ to accentuate the logs when the fire is not burning
- 100% SAFE GUARD™ gas control system automatically and quickly shuts off the gas supply for your peace of mind

Madison™ GD80 - 47" Direct Vent Gas Fireplace



- Heater rated and up to 43,000 BTU's
- 50% flame/heat adjustment for maximum comfort and efficiency
- Exclusive Night Light™ illuminates the decorative firebox and logs
- Elegant large cast iron andirons and grate
- Fully operable safety pull screen included
- Heat circulating blower standard with every unit
- Modulating thermostatic hand held remote that controls flame, heat, blower and Night Light™
- Immense 37"Wx 30"H clear, unobstructed view in a frameless finish through high temperature, heat radiating, ceramic glass
- Available in either an arched or rectangular opening
- Concealed, easy to use controls for trouble-free operation
- Bathroom, bedroom and bed sitting room approved — also suitable for mobile homes

WOOD BURNING STOVES

Pedestal

Napoleon's pedestal model wood burning stove features a solid, dynamic appearance with performance to match. The Pedestal model is designed to provide you with outstanding heat efficiencies while achieving low emissions. Comes standard with black louvers, black trivet & ash pan with lid.



Models Available:

1100	small stove	1500 sq. ft. - Heating
1400	medium stove	2000 sq. ft.- Heating
1900	large stove	3500 sq. ft.- Heating



Leg Models Available: 1100 and 1400

Colors Available: Painted Black, Porcelain Black, Almond, Green

Door Selection:	H222	Standard Arch - Painted Black
	H222-G	Standard Arch - Gold Plated
	H222-SS	Standard Arch - Satin Chrome Plated
	H222-W	Webbed Arch - Painted Black
	H222-GW	Webbed Arch - Gold Plated
	H222-SSW	Webbed Arch - Satin Chrome Plated

1100C - CAST IRON - EPA WOOD BURNING STOVE

Finishes Available:	Painted Black
	Wrought Iron
	Porcelain Enamel Majolica Brown

Accessories:	Blower
	Heatshield
	Screen



1150P - EPA WOOD GOURMET - COOK STOVE

Finish:	Painted Black	
Door Selection:	H222	Standard Arch - Painted Black
	H222-G	Standard Arch - Gold Plated
	H222-SS	Standard Arch - Satin Chrome Plated
	H222-W	Webbed Arch - Painted Black
	H222-GW	Webbed Arch - Gold Plated
	H222-SSW	Webbed Arch - Satin Chrome Plated



WOOD BURNING INSERTS

Wood Burning Inserts

Years of research, strict quality testing and patented wood burning technology have surpassed critical standards, providing you with the cleanest, most efficient wood burning inserts. Napoleon® regularly exceeds EPA (Environmental Protection Agency) standards, making a difference in keeping our environment clean.



- Large viewing area through an elegantly arched cast iron door
- Includes WHISPER QUIET™ heat circulating blower
- Economical 6" flue assures you of efficiency and cost saving installations
- Cool room air is circulated around the firebox, heated and returned to the room
- Non-catalytic high tech design eliminates the need for a delicate ceramic catalytic combustor which can deteriorate over time.
- President's Limited Lifetime Warranty

EPI - 1101 Wood Burning Insert



- Effective air wash in combination with high temperatures keeps the viewing glass clean
- Secondary air tube insulated with ceramic fibre and protected with a stainless steel cover plate ensures complete combustion
- Fully refractory lined firebox maintains the interior temperatures necessary to achieve low emissions and complete combustion
- The easy operation of a single lever burn control regulates primary and secondary air establishing a perfect mixture and providing a clean burn

Doors: Standard Arch or Early American webbed arched cast iron doors available in painted black, 24 karat gold plated or satin chrome plated finish

Cast Iron Surrounds: Painted Black, Porcelain Enamel Black, Porcelain Enamel Mojolica Brown, Porcelain Enamel Mojolica Green

Accessories: Spring door handle and air control handle in black, brass or satin chrome finish. Optional polished brass surround trim for flashing

EPI - 1402 Wood Burning Insert



- Complete with standard flashing/surround and trim to cover fireplace opening up to 32"H x 44"W
- Colors Available: Porcelain Enamel Black and Painted Black finish. Special order Porcelain Enamel Almond and Porcelain Enamel Green.

Doors: Standard arch cast iron doors available in painted black, 24 karat gold plated or satin chrome plated finish. Early American webbed arched cast iron doors available in painted black, 24 karat gold plated or satin chrome plated finish

Cast Iron Surrounds: Painted Black, Porcelain Enamel Black, Porcelain Enamel Mojolica Brown, Porcelain Enamel Mojolica Green

Accessories: Spring door handle and air control handle in black, brass or satin chrome finish. Optional polished brass surround trim for flashing

DIRECT VENT FIREPLACES

CDV DIRECT VENT FREE GAS FIREPLACE SYSTEM



- Glowing ceramic fiber logs featuring a patented Natural Flame aluminized pan burner with random dancing flames and large ember bed
- Millivolt with on/off switch and variable flame height control or electronic ignition in natural gas or propane gas
- Natural or propane field convertible
- Flexible connector with On/Off valve included
- Approved for installation with Simpson Dura Vent, Selkirk Metalbestos or Metal Fab Direct Vent Chimney
- Includes 15' of preinstalled millivolt wire
- Electrical junction box included for hook up
- Removable unitized black louver assembly for ease of installation
- Available in dedicated rear or top vent units
- Available in two sizes 33" or 36"



Model	Description
CDVR36NV	36" Rear Vent, Direct Vent Fireplace, Natural Gas, Millivolt Ignition
CDVR36PV	36" Rear Vent, Direct Vent Fireplace, Propane Gas, Millivolt Ignition
CDVT36NV	36" Top Vent, Direct Vent Fireplace, Natural Gas, Millivolt Ignition
CDVT36PV	36" Top Vent, Direct Vent Fireplace, Propane Gas, Millivolt Ignition

* Electronic ignition models and trim kits are available.

Call for details.

OUTDOOR FIREPLACES



HWB700OD



STAINLESS STEEL OUTDOOR/INDOOR RADIANT WOOD BURNING FIREPLACE

- 44"W x 27"H x 22"D firebox opening. Uses "L" series chimney.
- All-SS construction provides years of use and corrosion protection.
- Firebox interior offers a beautiful herringbone brick pattern with steel mesh reinforcements.
- For outdoor installations, firebox floor contains a draining system.

HWB700OD	Actual	Framing
Width	53 1/8"	53 5/8"
Height	52 7/8"	53 1/8"
Depth	26 3/8"	27 7/8"

LAVISTA Outdoor Gas Fireplace ODL 500



OUTDOOR SERIES LA VISTA UNVENTED FIREPLACE

- Available in 42" wide opening
- Stainless steel construction for outdoor applications
- Herringbone refractory firebrick lined for true masonry look
- Comes standard with 30" Weathered Pine refractory log set
- Stainless steel glass doors standard

SIGNATURE COMMAND CONTROL FEATURES (CSA BURNER ONLY)

- Battery operated electronic ignition
- Cold climate pilot option
- Hi/lo 3 step flame adjustment
- Touch button command center with wall cover
- Weatherproof stainless steel outdoor command center housing provided standard
- Optional hand held remote ready

Model #	Description
ODL500NSC	42" La Vista Outdoor Unvented SS Fireplace w/ Signature Command Control, Natural Gas
ODL500PSC	42" La Vista Outdoor Unvented SS Fireplace w/ Signature Command Control, Propane Gas
RMSC	Hand-Held Remote Control with On/Off, Hi/Lo FLame Adjustment and Timer Operation
SCSWEK	Signature Command System Wall Mount Extension Kit, (15ft. wire, rough-in box, wall cover)